Technical overview

JURA standards

Joixi standards	
Pulse Extraction Process	(P.E.P.®)
Variable VC brewing unit	from 5 g to 16 g
Intelligent Pre-Brew Aroma System	I.P.B.A.S. [©]
Electrically adjustable ceramic disc Grinder	1
High-performance pump	2 x 15 bar
Thermoblock heating system	2
Fluid system	2
JURA fine foam technology	
Milk system	HP3
Integrated rinsing, cleaning and descaling	
Integrated milk system rinsing and cleaning	
CLARIS filter (smart pro & smart maxi)	CLARIS smart
Energy Save Mode	E.S.M.©
Zero-Energy Switch	

Specific advantages

32
(A.G.A.©)
(I.W.S.®)
0.5 L / Min.



JURA SEA (Pte.) Ltd. 25 International Business Park, German Centre #01-01/10, Singapore 609916 Tel.: +65 65628853, Fax: +65 65628854, Email: info@jura-sea.com, Web: https://www.jura-sea.com

rogrammable Milk / Milk foam temperature 10 Level rogrammable amount of Milk / Milk foam 11 tore / copy personalize products 11 rogrammable temperature of hot water 3 Level rogrammable brewing temperature 3 Level rogrammable brewing temperature 3 Level eset the day counter 10 rogrammable switch-on / switch-off time 11 umber of preparations for each individual product 11 esign and materials 11 lu Frame Design® 3 mn 3" Display TFT color touch screen ED Illumination Amber / Whith owder chute for ground coffee 11 ound design 11 pecifications 11 eight-adjustable dual spout 70 – 159 mn eight-adjustable hot-water spout 69 – 165 mn /ater Tank Capacity (GIGA X3) 5.0 x Water Connection (GIGA X3c) 12 offee grounds container ca. 40 Serving ean container capacity 1 ka oltage / Power 220–240 V~ / 2,300V urrent 10 / 10 / 37 × 5	Programmable amount of water	
rogrammable amount of Milk / Milk foam tore / copy personalize products rogrammable temperature of hot water rogrammable brewing temperature eset the day counter rogrammable switch-on / switch-off time umber of preparations for each individual product esign and materials lu Frame Design® 3 mn 3" Display TFT color touch screen 2D Illumination Amber / Whith owder chute for ground coffee 1 ound design 1 pecifications 70 – 159 mn eight-adjustable dual spout 70 – 159 mn eight-adjustable hot-water spout 69 – 165 mn /ater Tank Capacity (GIGA X3) 5.0 x Water Connection (GIGA X3c) 1 offee grounds container ca. 40 Serving ean container capacity 1 k oltage / Power 220–240 V~ / 2,300V urrent 10 / tand-by power <0.5V	Programmable adjustable coffee strength	10 Levels
core / copy personalize products 3 rogrammable temperature of hot water 3 rogrammable brewing temperature 3 eset the day counter 1 rogrammable switch-on / switch-off time 1 umber of preparations for each individual product 1 esign and materials 3 lu Frame Design® 3 3" Display TFT color touch screen 2D Illumination Amber / Whith powder chute for ground coffee 1 pound design 1 pecifications 69 – 165 mm eight-adjustable dual spout 70 – 159 mm eight-adjustable hot-water spout 69 – 165 mm /ater Tank Capacity (GIGA X3) 5.0 x Water Connection (GIGA X3c) 1 offee grounds container ca. 40 Serving ean container capacity 1 oltage / Power 220–240 V~ / 2,300V urrent 10 tand-by power <0.5V	Programmable Milk / Milk foam temperatu	ire 10 Levels
rogrammable temperature of hot water3 Levelrogrammable brewing temperature3 Levelrogrammable brewing temperature3 Leveleset the day counter1rogrammable switch-on / switch-off time1umber of preparations for each individual product1esign and materials3 mn3" DisplayTFT color touch screen2D IlluminationAmber / Whitowder chute for ground coffee1ound design1pecifications69 – 165 mneight-adjustable dual spout70 – 159 mn/ater Tank Capacity (GIGA X3)5.0x Water Connection (GIGA X3c)1offee grounds containerca. 40 Servingean container capacity1 koltage / Power220–240 V~ / 2,300Vurrent10 /tand-by power< 0.5V	Programmable amount of Milk / Milk foam	
rogrammable brewing temperature 3 Level rogrammable brewing temperature 3 Level eset the day counter 1 rogrammable switch-on / switch-off time 1 umber of preparations for each individual product 1 esign and materials 3 mn lu Frame Design® 3 mn 3" Display TFT color touch screent ED Illumination Amber / Whith owder chute for ground coffee 1 pecifications 1 eight-adjustable dual spout 70 – 159 mn eight-adjustable hot-water spout 69 – 165 mn /ater Tank Capacity (GIGA X3) 5.0 x Water Connection (GIGA X3c) 1 offee grounds container ca. 40 Serving ean container capacity 1 k oltage / Power 220–240 V~ / 2,300V urrent 10 / tand-by power <0.5V	Store / copy personalize products	
eset the day counter rogrammable switch-on / switch-off time umber of preparations for each individual product esign and materials lu Frame Design® 3 mm 3" Display TFT color touch screen Dillumination Amber / Whit owder chute for ground coffee ound design 1 pecifications eight-adjustable dual spout 70 – 159 mm eight-adjustable hot-water spout 69 – 165 mm /ater Tank Capacity (GIGA X3) 5.0 x Water Connection (GIGA X3) 7.0 x Y X X X X X X X X X X X X X X X X X X	Programmable temperature of hot water	3 Levels
rogrammable switch-on / switch-off time umber of preparations for each individual product esign and materials lu Frame Design® 3 mm 3" Display TFT color touch screen Dillumination Amber / Whit owder chute for ground coffee bund design 1 pecifications eight-adjustable dual spout 70 – 159 mm eight-adjustable hot-water spout 69 – 165 mm /ater Tank Capacity (GIGA X3) 5.0 x Water Connection (GIGA X3) 5.0	Programmable brewing temperature	3 Levels
umber of preparations for each individual product esign and materials lu Frame Design® 3 mm 3" Display TFT color touch screen DIllumination Amber / White owder chute for ground coffee 1 ound design 1 pecifications 70 – 159 mm eight-adjustable dual spout 70 – 159 mm //ater Tank Capacity (GIGA X3) 5.0 x Water Connection (GIGA X3c) 1 offee grounds container ca. 40 Serving ean container capacity 1 km oltage / Power 220–240 V~ / 2,300V urrent 10 / tand-by power <0.5V	Reset the day counter	
esign and materials lu Frame Design® 3 mm 3" Display TFT color touch screen DIllumination Amber / White owder chute for ground coffee 1 ound design 1 pecifications 70 – 159 mm eight-adjustable dual spout 69 – 165 mm /ater Tank Capacity (GIGA X3) 5.0 x Water Connection (GIGA X3c) 1 offee grounds container ca. 40 Serving ean container capacity 1 km oltage / Power 220–240 V~ / 2,300V urrent 10 / tand-by power < 0.5V	Programmable switch-on / switch-off time	
lu Frame Design® 3 mm 3" Display TFT color touch screet 2D Illumination Amber / Whit owder chute for ground coffee 1 ound design 1 pecifications 70 – 159 mm eight-adjustable dual spout 69 – 165 mm /ater Tank Capacity (GIGA X3) 5.0 x Water Connection (GIGA X3c) 1 offee grounds container ca. 40 Serving ean container capacity 1 oltage / Power 220–240 V~ / 2,300V urrent 10 / tand-by power < 0.5V	Number of preparations for each individua	l product
lu Frame Design® 3 mm 3" Display TFT color touch screet 2D Illumination Amber / Whit owder chute for ground coffee 1 ound design 1 pecifications 70 – 159 mm eight-adjustable dual spout 69 – 165 mm /ater Tank Capacity (GIGA X3) 5.0 x Water Connection (GIGA X3c) 1 offee grounds container ca. 40 Serving ean container capacity 1 oltage / Power 220–240 V~ / 2,300V urrent 10 / tand-by power < 0.5V /eight 19 k imensions (W x H x D) 37 × 56.5 × 49.7 cm olor Aluminium		
3" Display TFT color touch screen ED Illumination Amber / Whit owder chute for ground coffee Image: Construction of the screen ound design TO – 159 mm eight-adjustable dual spout 70 – 159 mm eight-adjustable hot-water spout 69 – 165 mm /ater Tank Capacity (GIGA X3) 5.0 x Water Connection (GIGA X3c) Image: Construction of the screen offee grounds container ca. 40 Serving ean container capacity 1 km oltage / Power 220–240 V~ / 2,300V urrent 10 / tand-by power < 0.5V	Design and materials	
ED Illumination Amber / Whit owder chute for ground coffee Image: Construction of the second design pecifications 70 – 159 mm eight-adjustable dual spout 70 – 159 mm eight-adjustable hot-water spout 69 – 165 mm /ater Tank Capacity (GIGA X3) 5.0 x Water Connection (GIGA X3) 5.0 offee grounds container ca. 40 Serving ean container capacity 1 km oltage / Power 220–240 V~ / 2,300V urrent 10 / tand-by power < 0.5V	Alu Frame Design®	3 mm
owder chute for ground coffee Image: Source of the sourc	4.3" Display	TFT color touch screen
pund design 70 – 159 mm eight-adjustable dual spout 70 – 159 mm eight-adjustable hot-water spout 69 – 165 mm /ater Tank Capacity (GIGA X3) 5.0 x Water Connection (GIGA X3c) 50 offee grounds container ca. 40 Serving ean container capacity 1 km oltage / Power 220–240 V~ / 2,300V urrent 10 / tand-by power < 0.5V	LED Illumination	Amber / White
pecifications eight-adjustable dual spout 70 – 159 mm eight-adjustable hot-water spout 69 – 165 mm /ater Tank Capacity (GIGA X3) 5.0 x Water Connection (GIGA X3c) 5.0 offee grounds container ca. 40 Serving ean container capacity 1 km oltage / Power 220–240 V~ / 2,300V urrent 10 / tand-by power < 0.5V	Powder chute for ground coffee	
eight-adjustable dual spout70 – 159 mmeight-adjustable hot-water spout69 – 165 mm/ater Tank Capacity (GIGA X3)5.0x Water Connection (GIGA X3c)1offee grounds containerca. 40 Servingean container capacity1 kmoltage / Power220–240 V~ / 2,300Vurrent10 /tand-by power< 0.5V	Sound design	
eight-adjustable dual spout70 – 159 mmeight-adjustable hot-water spout69 – 165 mm/ater Tank Capacity (GIGA X3)5.0x Water Connection (GIGA X3c)1offee grounds containerca. 40 Servingean container capacity1 kmoltage / Power220–240 V~ / 2,300Vurrent10 /tand-by power< 0.5V		
eight-adjustable hot-water spout69 - 165 mm/ater Tank Capacity (GIGA X3)5.0x Water Connection (GIGA X3c)1offee grounds containerca. 40 Servingean container capacity1 kgoltage / Power220-240 V~ / 2,300Vurrent10 /tand-by power< 0.5V	Specifications	
/ater Tank Capacity (GIGA X3) 5.0 x Water Connection (GIGA X3c)	Height-adjustable dual spout	70 – 159 mm
x Water Connection (GIGA X3c)offee grounds containerca. 40 Servingean container capacityoltage / Power220-240 V~ / 2,300Vurrent10 /tand-by power< 0.5V	Height-adjustable hot-water spout	69 – 165 mm
x Water Connection (GIGA X3c)offee grounds containerca. 40 Servingean container capacityoltage / Power220-240 V~ / 2,300Vurrent10 /tand-by power< 0.5V	Water Tank Capacity (GIGA X3)	5.0 L
ean container capacity 1 k oltage / Power 220–240 V~ / 2,300V urrent 10 / tand-by power < 0.5V /eight 19 k imensions (W x H x D) 37 × 56.5 × 49.7 cm olor Aluminium	Fix Water Connection (GIGA X3c)	
oltage / Power 220–240 V~ / 2,300V urrent 10 / tand-by power < 0.5V	Coffee grounds container	ca. 40 Servings
urrent 10 / tand-by power < 0.5V	Bean container capacity	1 kg
tand-by power < 0.5V	Voltage / Power	220–240 V~ / 2,300W
//eight 19 km imensions (W x H x D) 37 × 56.5 × 49.7 cm olor Aluminium	Current	10 A
imensions (W x H x D) 37 × 56.5 × 49.7 cm olor Aluminium	Stand-by power	< 0.5W
olor Aluminiun	Weight	19 kg
	Dimensions (W x H x D)	37 × 56.5 × 49.7 cm
rticle Number GIGA X3 / X3c 15299 / 15230	Color	Aluminium
	Article Number GIGA X3 / X3c	15299 / 15230

JURA GIGA X3 ALU







Easy operation thanks to TFT Touch Screen



Speed Function for a faster preparation



Large aroma sealed coffee bean container



Automated Cleaning of Milk System

JURA GIGA X3 aluminium

A flexible move into the top class

The GIGA X3 allows JURA to impressively demonstrate Swiss innovation and professionalism down to the very last detail. Anywhere where a capacity of up to 150 cups is the order of business, the machine impresses users with its quality, functionality and reliability. Coupled with top performance in every respect, this results in a high-tech automatic coffee machine that is ideally tailored to the requirements of large offices, the breakfast, seminar and conference venue sectors as well as self-service areas.

State-of-the-art technologies for perfect enjoyment

It's all inside the GIGA X3: The high-performance ceramic disc grinder guarantees reliable grinding results for many years which are sure to be precise, consistent and even. A top innovation provides that extra special something: A.G.A.[©] (Automatic Grinder Adjustment) – the electronically controlled automatic readjustment system. The Pulse Extraction Process (P.E.P.[®]) optimizes the extraction time for short specialities and CLARIS Pro Smart delivers perfect water quality for a pure taste in combination with the Intelligent Water System (I.W.S.[®]). The GIGA X3 features a sophisticated height-adjustable dual spout, which finishes off trend specialities with milk and milk foam to perfection thanks to fine foam technology. The speed function ensures speciality coffees in record time. Time spent topping the machine up is reduced to a minimum thanks to the large bean container with a holding capacity of 1 kg and aroma preservation cover. What's more, the high capacity of the 5.0L water tank for X3, fix Water Connection for X3c and the large coffee grounds container maximise autonomy.

TÜV-certified hygiene guarantee

Maintenance of the GIGA X3 is just as straightforward, logical and intuitive as its operation. Original JURA maintenance products and integrated rinsing and cleaning programmes ensure TÜV-certified hygiene at the touch of a button. The milk system is also very easy to clean. The fully automatic process is started with just a touch on the display and ensures perfect cleanliness.

PROFESSIONAL



Preparation Times







1 Minute 18 s

2 Cappuccino

2 Espressi 38 seconds 56 seconds 2 Cafe Creme 1 minute 1 s

2 Cafe Latte 1 minute 10 s

SWISS MADE



2 Latte Macchiati 1 minute 29 s



Pot (360 ml) 1 Minute 57 s



Hot Water (200 ml) 27 seconds